

### **Amendment to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in this Application.

### **Listing of Claims:**

1. (Currently Amended) Line guide device for guiding lines, comprising a plurality of links, connected to each other in articulated fashion, where at least some, or all, of the links each display a bottom element, opposite side walls and at least one cover element, forming a duct for accommodating lines, where the plurality of links are integrally ~~moulded~~ molded on one another in one piece, forming a continuous strand, and where the line guide device can be arranged to form a lower run, a curved section and an upper run, where the bottom element and both opposite side walls of the links are designed in one piece as U-sections that are essentially rigid under the intended loads, and where the cover element of the respective link is integrally ~~moulded~~ molded on at least one side wall of said link and designed to be moveable relative to the side wall, and can be moved into a position closing the link and a position at least essentially releasing the area between the opposite side walls, characterized in that mutually corresponding stops of adjacent links are provided, which interact in the straight position or curved position or both of the line guide device and are in each case located on the cover elements of the adjacent links or are provided by overlapping areas of adjacent links in the form of tabs, which are integrally ~~moulded~~ molded in one piece on the side walls or cover elements or both of at least some links and, starting from a first position, can be moved into a second position, in which they overlap a partial area of an adjacent link.

2. (Previously Presented) Line guide device according to claim 1, characterised in that the line guide device is manufactured as a one-piece plastic part.

3. (Currently Amended) Line guide device according to claim 1, characterised in that a closing means, integrally ~~moulded~~ molded in one piece, is provided on the cover element being connectable in detachable fashion to a corresponding closing means to form a line guide device that is closed on the cover side, where the

corresponding closing means is located on the side wall of the respective link, or in that the cover element is of two-part design and the closing element is integrally ~~moulded~~ molded in one piece on the cover element part of the respective link opposite the first cover element part.

4. (Currently Amended) Line guide device according to claim 1, characterised in that said mutually corresponding stops of adjacent links ~~are provided with stops that~~ correspond to each other and come into contact with each other when the line guide device is in the straight position, and in that at least one of ~~the said~~ corresponding stops of adjacent links is provided on a cover element or on the inner sides of the side walls facing towards the duct or the outer sides of the side walls facing away from the duct or the upper side of the side wall facing away from the bottom element of the link or a combination of them.

5. (Previously Presented) Line guide device according to claim 1, characterised in that the stop is designed as an area of the cover element which, in the straight position of the line guide device, projects onto the adjacent link and, in stop position, engages a recess provided with a stop in a cover element of a side wall of the adjacent link.

6. (Previously Presented) Line guide device according to claim 1, characterised in that the cover elements of the line guide device are designed in such a way that they provide a closed upper side of the line guide device in the straight position of the line guide device.

7. (Previously Presented) Line guide device according to claim 1, characterised in that the cover elements of the line guide device are designed in such a way that they also provide a closed upper side of the line guide device in the curved position of the line guide device.

8. (Currently Amended) Line guide device according to claim 1, characterised in that at least some cover elements of the links are provided with at least one integrally ~~moulded~~ molded projecting area, which forms overlapping areas with at least one of the respectively adjacent links in the straight or curved position of the line guide device or both, and in that stop elements acting in stop position are located on the overlapping areas of the respectively adjacent links.

9. (Currently Amended) Line guide device according to claim 1, characterised in that at least some cover elements are provided on both sides with integrally ~~moulded~~ molded projecting areas, which project towards both adjacent links and in each case overlap the cover element of the adjacent links, or projecting areas projecting from the adjacent cover elements towards the respective link.

10. (Previously Presented) Line guide device according to claim 1, characterised in that the stop is designed as a peg projecting from the respectively overlapping area transverse to the longitudinal direction of the line guide device, and in that the respectively corresponding stop displays a recess receiving the peg, in which the peg is accommodated over at least part, or all, of the pivoting movement of adjacent links relative to each other.

11. (Previously Presented) Line guide device according to claim 1, characterised in that, in the straight position of the line guide device, the face ends of the side walls of respectively adjacent links that face each other are spaced apart from each other, at least over part, or all, of their height.

12. (Previously Presented) Line guide device according to claim 1, characterised in that the bottom element or the side wall of at least one, or both, of the respectively adjacent links is provided with a projection, which projects onto the adjacent link and, in the curved position of the line guide device, can be brought into contact with an opposite area of the adjacent link.

13. (Currently Amended) Line guide device according to claim 1, characterised in that fastening elements corresponding to each other are integrally ~~moulded~~ molded in one piece on the ends of the line guide device, by means of which the line guide device can be assembled to a line guide device of identical design, extending the length of the same.

14. (Previously Presented) Line guide device according to Claim 13, characterised in that at least one fastening element is provided on one end thereof, and corresponding fastening elements are provided on several or all links of the line guide device, these being connectable to each other, at least after adjusting the length of the line guide device.

15. (Previously Presented) Line guide device according to claim 1, characterised in that, on at least some links, at least one dividing web is provided between opposite side walls of the link, which acts as a partition for the interior space and is connected to the bottom element in one piece.

16. (Previously Presented) Line guide device according to claim 1, characterised in that at least some cover elements of the links engage at least one, or both, of the adjacent links and are located with an area between opposite side walls of the respectively adjacent link, and in that the area located between the side walls displays a width essentially corresponding to the distance between the side walls.

17. (Previously Presented) Line guide device according to claim 1, characterised in that the line guide device displays, over at least essentially the length of the bottom element interconnecting several links, or over a distance in the longitudinal direction of the line guide device between two adjacent links that are earthed or provided with an earthing device, which are preferably connected to each other via a continuous bottom element, or over the full length of the line guide device, an electrical resistance R of approx. 20,000 ohms or less.

18. (Previously Presented) Line guide device according to claim 1, characterised in that the line guide device displays, over at least essentially the length of a continuous bottom element interconnecting several links, or over a distance in the longitudinal direction of the line guide device between two adjacent links that are earthed or provided with an earthing device, which are preferably connected to each other via the continuous bottom element, or over the full length of the line guide device, an electrical surface resistance  $R_s$  or an end-to-end resistance  $R_e$  or a point-to-point resistance  $R_p$  of  $\leq 1 \times 10^{10}$  ohms.

19. (Previously Presented) Line guide device according to claim 1, characterised in that the line guide device displays, over at least essentially the length of a continuous bottom element interconnecting several links, or over a distance in the longitudinal direction of the line guide device between two adjacent links that are earthed or provided with an earthing device, which are preferably connected to each other via the continuous bottom element, or over the full length of the line guide device, an electrical resistance of  $R_g \leq 1 \times 10^{12}$  ohms to an EPA earthing point connected to the line guide device, or to an EPA earthing device connected to the line guide device.

20. Cancelled